

LOW VOLTAGE 230V

Lamp details	LT5-B5-HE+HO LT5-R5-HE+HO	LT8-B8 LT8-R8	LT8-B5-HE LT8-R5-HE	LT12-B8 LT12-R8
Lamp diameter (mm)	16	26	26	38
Electrode diameter (mm)	16	26	16	26
Minimum length (mm)	400	450	400	1,250
Maximum length (mm)	1,370	1,700	1,370	1,700
Base	G5	G13	G5	G13
Average lifespan (working hours)	30,000	35,000	35,000	35,000

Lamp options	LT5-B5-HE+HO LT5-R5-HE+HO LT8-B5-HE LT8-R5-HE	LT8-B8 LT8-R8 LT12-B8 LT12-R8
Non-dimmable	v	v
Dimmable	v	v*
Interior use	v	v
Exterior use	-	v**
Electronic ballast 230 V	v	v

* option dimmable is not available for LT8-B8-70, LT8-R8-70, LT12-B8-70 and LT12-R8-70

** for use outdoors, IP64 G13 connectors and a ballast in a watertight outdoors kit must be used

Colours

WHITE COLOURS	RGB
Comfort white 827 - 2,700K	R - red 804
Warm white 830 - 3,000K	G - green 803
Neutral white 840 - 4,000K	B - blue 801
Cold white 865 - 6,500K	
OTHER COLOURED POWDERS / GLASS:	ON REQUEST

Lighting Control Systems

Switchdim DS1	with push button for operating a maximum of 5 ballasts
Switchdim DS2	with push button and module for operating a maximum of 25 ballasts
Analogue 1-10V direct voltage control (DAD)	with dimmer module
Control using IR remote control (DIR)	with IR module
Dali lighting control system	with DIM DALI ballast + Dali components

Lumen output	LT5-B5-HE	LT5-R5-HE
	LT8-B5-HE	LT8-R5-HE
POWER (WATT)	LUMEN OUTPUT * (LUM)	
14w	1,350	
21w	2,100	
28w	2,900	
35w	3,650	
average lumen output	3,000 lum/m	

	LT5-B5-HO	LT5-R5-HO
	POWER (WATT)	LUMEN OUTPUT * (LUM)
24w	1,750	
39w	3,100	
54w	4,450	
80w	6,150	
average lumen output	4,200 lum/m	

	LT8-B8	LT8-R8
	LT12-B8	LT12-R8 <i>(only available with 58 and 70w)</i>
POWER (WATT)	LUMEN OUTPUT * (LUM)	
18w	1,350	
30w	2,400	
36w	3,350	
58w	5,200	
70w	6,200	
average lumen output	3,400 lum/m	

* lumen output for maximum available length